



Item # _____

Job _____

HD SUPER™ WORK CENTERS

- **Heavy-Duty:** HD Super™ Work Centers are designed and built for heavy-duty applications. The work surface is made of seamless, 14-gauge stainless steel with an 11-gauge support structure that virtually eliminates any “drumming”.
- **Greater Rigidity:** Work Centers features 1½" diameter HD Super™ posts and the tapered sleeves and corners of patented Super Erecta Shelf® construction. These two features assure a rigid, wobble-free table.
- **Easy to Assemble:** Units are shipped knocked down and can be put together in minutes without special tools. Bottom shelf of frame is adjustable in 2" (51mm) increments. The table top fits over plastic sleeves at the top of the posts.
- **Several Styles Available:** Versatile HD Super™ Work Centers come in 24 models, all with stainless steel tops, but offering a choice of chrome-plated or stainless steel posts and either a shelf or a three-sided frame which can be placed at the desired level below the top. Additional shelves can be ordered from HD Super™ stock.
- **Stationary or Mobile:** Standard units are stationary with leveling foot on each post. Work Centers are also available fitted with 5" (127mm) polyurethane swivel casters, two with wheel brake.
- **Popular Sizes:** Work Centers come in 30" (760mm), 36" (910mm) and 44" (1118mm) widths and lengths of 60", 72" and 96" (1525, 1825 and 2440mm). All models are 34" (860mm) high.



Work Center with Shelf.
Deluxe Drawer shown
sold separately.



Work Center with
3-Sided Tubular Frame



InterMetro Industries Corporation
North Washington Street
Wilkes-Barre, PA 18705
www.metro.com

Copyright © 2000 InterMetro Industries Corp.



Work Center with
“H” Frame

Dimensions

Standard Work Centers

30" (760mm) Wide

| Cat. No. | Length | | Post Material | Bottom Shelf Material (16 ga.) | Bottom 3-Sided Frame Material (16 ga.) | Bottom H-Frame Material (16 ga.) | Approx. Pkd. Wt. | |
|----------|--------|------|---------------|--------------------------------|--|----------------------------------|------------------|------|
| | (in.) | (mm) | | | | | (lbs.) | (kg) |
| WT306FS | 60 | 1525 | SS | SS | — | — | 121 | 55 |
| WT307FS | 72 | 1825 | SS | SS | — | — | 139 | 63 |
| WT309FS | 96 | 2439 | SS | SS | — | — | 169 | 77 |
| WT306FC | 60 | 1525 | Chrome | Galvanized | — | — | 121 | 55 |
| WT307FC | 72 | 1825 | Chrome | Galvanized | — | — | 139 | 63 |
| WT309FC | 96 | 2439 | Chrome | Galvanized | — | — | 169 | 77 |
| WT306US | 60 | 1525 | SS | — | SS | — | 104 | 47 |
| WT307US | 72 | 1825 | SS | — | SS | — | 121 | 55 |
| WT309US | 96 | 2439 | SS | — | SS | — | 150 | 68 |
| WT306HS | 60 | 1525 | SS | — | — | SS | 104 | 47 |
| WT307HS | 72 | 1825 | SS | — | — | SS | 120 | 54 |
| WT309HS | 96 | 2439 | SS | — | — | SS | 150 | 68 |

Load Ratings: 60" long units-625 lbs. (283kg); 72" long units-750 lbs. (340 kg); 96" long units-1000 lbs. (454kg), equally distributed.

Standard Work Centers

36" (910mm) Wide

| Cat. No. | Length | | Post Material | Bottom Shelf Material (16 ga.) | Bottom 3-Sided Frame Material (16 ga.) | Bottom H-Frame Material (16 ga.) | Approx. Pkd. Wt. | |
|----------|--------|------|---------------|--------------------------------|--|----------------------------------|------------------|------|
| | (in.) | (mm) | | | | | (lbs.) | (kg) |
| WT366FS | 60 | 1525 | SS | SS | — | — | 129 | 59 |
| WT367FS | 72 | 1825 | SS | SS | — | — | 149 | 68 |
| WT369FS | 96 | 2439 | SS | SS | — | — | 182 | 83 |
| WT366FC | 60 | 1525 | Chrome | Galvanized | — | — | 129 | 59 |
| WT367FC | 72 | 1825 | Chrome | Galvanized | — | — | 149 | 68 |
| WT369FC | 96 | 2439 | Chrome | Galvanized | — | — | 182 | 83 |
| WT366US | 60 | 1525 | SS | — | SS | — | 112 | 51 |
| WT367US | 72 | 1825 | SS | — | SS | — | 131 | 59 |
| WT369US | 96 | 2439 | SS | — | SS | — | 163 | 74 |
| WT366HS | 60 | 1525 | SS | — | — | SS | 112 | 51 |
| WT367HS | 72 | 1825 | SS | — | — | SS | 130 | 59 |
| WT369HS | 96 | 2439 | SS | — | — | SS | 163 | 74 |

Load Ratings: 60" long units-625 lbs. (283kg); 72" long units-750 lbs. (340 kg); 96" long units-1000 lbs. (454kg), equally distributed.

Dimensions

Standard Work Centers

44" (1118mm) Wide

| Cat. No. | Length | | Post Material | Bottom Shelf Material (16 ga.) | Bottom 3-Sided Frame Material (16 ga.) | Bottom H-Frame Material (16 ga.) | Approx. Pkd. Wt. | |
|----------|--------|------|---------------|--------------------------------|--|----------------------------------|------------------|------|
| | (in.) | (mm) | | | | | (lbs.) | (kg) |
| WT446FS | 60 | 1525 | SS | SS | — | — | 155 | 70 |
| WT447FS | 72 | 1825 | SS | SS | — | — | 174 | 79 |
| WT449FS | 96 | 2439 | SS | SS | — | — | 217 | 98 |
| WT446FC | 60 | 1525 | Chrome | Galvanized | — | — | 155 | 70 |
| WT447FC | 72 | 1825 | Chrome | Galvanized | — | — | 174 | 79 |
| WT449FC | 96 | 2439 | Chrome | Galvanized | — | — | 212 | 98 |
| WT446US | 60 | 1525 | SS | — | SS | — | 138 | 63 |
| WT447US | 72 | 1825 | SS | — | SS | — | 155 | 70 |
| WT449US | 96 | 2439 | SS | — | SS | — | 193 | 88 |
| WT446HS | 60 | 1525 | SS | — | — | SS | 137 | 62 |
| WT447HS | 72 | 1825 | SS | — | — | SS | 155 | 70 |
| WT449HS | 96 | 2439 | SS | — | — | SS | 193 | 88 |

Load Ratings: 60" long units-625 lbs. (283kg); 72" long units-750 lbs. (340 kg); 96" long units-1000 lbs. (454kg), equally distributed.

Accessories

Economy Drawer

| Cat. No. | Overall Dimensions Width/Length/Height | | Dimensions Inside Bottom | | Approx. Pkd. Wt. | |
|----------|--|-------------|--------------------------|---------|------------------|------|
| | (in.) | (mm) | (in.) | (mm) | (lbs.) | (kg) |
| WTD21C | 14 ¹ / ₄ x28x5 ³ / ₄ | 362x711x146 | 10x16 | 254x406 | 6.8 | 3.1 |



Deluxe Drawer

| Cat. No. | Overall Dimensions Width/Length/Height | | Dimensions Inside Bottom | | Approx. Pkd. Wt. | |
|----------|--|-------------|--------------------------|---------|------------------|------|
| | (in.) | (mm) | (in.) | (mm) | (lbs.) | (kg) |
| WTD51S | 24x25 ³ / ₄ x7 ¹ / ₂ | 610x654x191 | 20x20 | 508x508 | 31 | 13.9 |

