

Technical Specifications**Webbing anchorage sling****References:**

0.6 m 1002916

0.8 m 1002917

1 m 1003245

1.2 m 1002918

1.5 m 1002919

Features:**Yellow webbing:**

Material: Polyester 23 mm

Breaking strength: > 1000 daN

Tubular webbing :

24mm

Breaking strength: > 1150 daN



Sling in m	0.6	0.8	1	1.2	1.5
Colours	Blue	purple	green	black	red
Material	PES	PES	PES	PES	PES
Weight in Kg	0.104	0.119	0.138	0.178	0.214

PA : Polyamide

PES : Polyester

Tests:

Static test: > 1500 daN

Temperature : +50°C

EN 795 B : Anchorage devices – class B

LAW of 19 MARCH 93

PPE are products classified in category III, mortal risks, and as such they have to be the object of a periodic inspection for less than twelve months at the time of its use by the qualified person.

For more information, please contact our technical team at 02 48 52 40 42 or by e-mail techniserv.hsp@honeywell.com

HONEYWELL FALL PROTECTION FRANCE SAS

35-37 rue de la Bidauderie

F - 18100 Vierzon - France

Tel : +33 2 48 52 40 40

Fax : +33 2 48 71 04 97

Web site : www.honeywellsafety.com