



**PRODUCT NUMBER: R60X**  
**Redcote Plus - R60X**

Handling in an aggressive environment: oils, greases, chemicals, hydrocarbons. Chemical and petrochemical industry.

**Honeywell**

## Overview

**Reference Number**

R60X

**Product Type**

Gloves

**Range**

Chemical Protection

**Line**

Heavy chemical

**Brand**

Honeywell

**Brand formerly known as**

NORTH

**Industry**

- Agriculture
- Chemical Industries
- Petro-chemical
- Water treatment

**Product Use**

Handling in an aggressive environment: oils, greases, chemicals, hydrocarbons. Chemical and petrochemical industry.

## Features & Benefits

**Feature**

Red PVC glove Dipped on cotton liner Smooth finish

**Benefit**

**COMFORT** The cotton interlock lining absorbs hand perspiration for added comfort. Its smooth finish offers an excellent touch and increases dexterity. The glove's articulated fingers offer superior comfort and reduce effort in cases extended use. **RESISTANCE** Its PVC composition has been tailored for multi-purpose and repetitive handling in an oily atmosphere. The cotton interlock lining strengthens the glove's mechanical performance. Low resistance to ketones, aromatic and halogen hydrocarbons. **SAFETY** As a result of its superior quality PVC and being part of PPE Class III, it ensures excellent follow-up on quality. The cuff helps to protect a large part of the forearm. **HYGIENE** Sanitized treatment

**Technical Description**

**Description**

Red PVC glove Dipped on cotton liner Smooth finish

**Product Technology**

Dipped

**Glove/liner color**

Red

**Coating Type**

PVC

**Length**

40 cm

**Thickness**

1,4 mm

**Harmlessness**

In conformity with the European standards.

**Dexterity**

Class 5

**Sizes**

9L, 10XL

**EN 388 - Mechanical Hazards Abrasion Resistance**

Abrasion resistance	4
Cutting resistance (Coupe test)	1
Tear resistance	2
Puncture resistance	1
Cutting resistance (TDM test)	X

**EN ISO 374-1 Resistance to**

Resistance to permeation by chemicals	Type A - AKLNOT
---------------------------------------	-----------------

**EN 374-3 Resistance to**

Resistance to permeation by chemicals	AKL
---------------------------------------	-----

**Certifications**

**EU Category PPE**

3

**EU Certification**

0075/797/162/01/19/0354 EXT 01/01/19

**Certifications**

- EN 0075/797/162/05/13/0457 EXT 02/05/13

## Additional Information

### User Manual

UI 104

## Maintenance

### Storage Information

Minimum packaging : 12 pairs Cartons of 48 pairs.

### Care Instructions

In order to keep its properties, this article should not be cleaned.