



PRODUCT INFORMATION SHEET

James Briggs Ltd, Salmon Fields,
Royton, Oldham,
OL2 6HZ Tel No 0161627 0101

SVTQ750BLKLMK	BLACK LINEMARKER
SVTQ750BLMK	BLUE LINEMARKER
SVTQ750GLMK	GREEN LINEMARKER
SVTQ750RLMK	RED LINEMARKER
SVTQ750WLMK	WHITE LINEMARKER
SVTQ750YLMK	YELLOW LINEMARKER

1. Introduction

An acrylic resin based survey marking aerosol paint. Ideal for use by contractors / surveyors where high visibility marking is required.

2. Where to use

For general application to most conventional flooring including concrete, timber, tarmac and composites.

3. Where not to use

- On surfaces seen or suspected of being unsound, without first ascertaining appearance and performance on an inconspicuous area.

4. Benefits

- Narrow, well defined spray pattern allows letters, numbers and symbols to be marked easily.
 - Touch dry in less than 5 minutes.
 - Weather resistant – lasts around 3-6 months*
 - Available in a range of highly visible colours.
- *Dependant on atmospheric conditions and traffic, guide only.

5. Physical properties [Finish bases except where stated].

Appearance	A smooth homogeneous liquid with a characteristic solvent odour.
pH	Not applicable
Specific Gravity	1.140 – 1.180 [Typical]
Flammability, as Supplied	Extremely flammable, flash point below -20°C.
Composition Data, as Supplied	A solution of acrylic resin in a predominately ketonic solvent system, with micronised pigments, extenders & plasticizers, in a butane/propane/isobutane based propellant.
Volatile Organic content	575 – 600 gm/litre [Typical]
Service Temperature	Designed for use at ambient temperatures.

6. Application Details

Ensure surface is clean dry and sound. Shake the can vigorously until agitator ball moves freely. Spray approximately 15cm from the surface. After use, point can upwards and depress actuator for 3 or 4 seconds to clear the orifice.

7. Availability

750 ml Aerosols. Other colours are available upon request.

Version June 2021 MP7771, JR282, MP7781, MP7780, MP7769, JR084

This information is provided in good faith based upon data and sources believed to be reliable and correct. Conditions of use, outside the control of the Company, dictate that no responsibility can be assumed for the ultimate performance of this product.