



Prod. Ref.	26410-000
Safety cat.	S3 CI HRO SRC
Range of sizes	39 - 48 (6 - 13)
Weight (sz. 8)	810 g
Shape	C
Width (3 - 6)	10
Width (6,5 - 13)	11

Description: Black water repellent printed leather ranger boot, ecological fur lining, antistatic, anti-shock, slipping resistant, non metallic **APT Plate** midsole **Zero Perforation**.

Plus: Cold protection thanks to **THINSULATE™ B200**. Footbed **AIR** made of EVA and fabric, antistatic, anatomic, holed, antistatic. It guarantees high stability thanks to its different thicknesses in the plantar area. **ANTI TORSION SUPPORT** made of polycarbonate and fibreglass conveniently placed between heel and sole, which provides support and protection of the plantar arch, thus preventing harmful bendings and/or unwilling torsion. Outsole resistant to +300°C (1 minute contact). Padded collar. Internal side zip. Polyurethane toe cap protection.

Suggested uses: Engineering jobs, maintenance jobs, buildings, industries.

Care and maintenance: Clean after each use and dry off away from direct heat; treat the leather with a suitable shoe-polish. Avoid contact with aggressive chemicals or extreme temperature. Avoid immersion in sea water, lime water or cement mixed with water.

MATERIALS / ACCESSORIES

SAFETY TECHNICAL SPECIFICATIONS

		Clause EN ISO 20345:2011	Description	Unit	Cofra result	requirement
Complete shoe	Toe cap: non metallic TOP RETURN toe cap, impact resistant until 200 J and compression resistant until 1500 kg	5.3.2.3	Shock resistance (clearance after shock)	mm	16,5	≥ 14
		5.3.2.4	Compression resistance (clearance after compression)	mm	16	≥ 14
	Anti perforation midsole: in multi-layers highly tensile fabric, penetration resistant, Zero Perforation	6.2.1	Penetration resistance	N	To 1100 N	≥ 1100
Antistatic shoe: the bottom is fit for the dissipation of electrostatic charges		6.2.2.2	Electric resistance		No Perforation	
			- wet	MΩ	116	≥ 0.1
			- dry	MΩ	450	≤ 1000
Cold insulation		6.2.3.2	Cold insulation (temp. decrease after 30' C at -17 °C)	°C	8,5	≤ 10
			Energy absorption system: polyurethane low density and heel profile	6.2.4	Shock absorption	J
Upper	Black water repellent printed leather thickness 1,6/1,8 mm	5.4.6	Water vapour permeability	mg/cmq h	> 2,4	≥ 0,8
			Permeability coefficient	mg/cmq	> 26,3	> 15
		6.3.1	Water absorption		14%	≤ 30%
			Water penetration		0,0 g	≤ 0,2 g
Lining	Ecological fur, breathable, abrasion resistant, colour dark grey thickness 1,2 mm	5.5.3	Water vapour permeability	mg/cmq h	> 5,9	≥ 2
			Permeability coefficient	mg/cmq	> 47,4	≥ 20
Sole	PU/Nitrile rubber, antistatic, resistant to high temperatures, directly injected in the upper: Outsole: black nitrile rubber, slipping resistant, abrasion resistant, hydrocarbons resistant and heat resistant. Midsole: black PU, low density, comfortable and anti-shock. Adherence coefficient of the sole	5.8.3	Abrasion resistance (lost volume)	mm ³	95	≤ 150
		5.8.4	Flexing resistance (cut increase)	mm	2	≤ 4
		5.8.6	Interlayer bond strength	N/m	> 5	≥ 4
		6.4.4	Hot resistance (300 °C)	----	any melting	any melting
		6.4.2	Hydrocarbons resistance (ΔV = volume increase)	%	+ 2,7	≤ 12
		5.3.5	SRA : ceramic + detergent solution – flat		0,36	≥ 0,32
			SRA : ceramic + detergent solution – heel (contact angle 7°)		0,32	≥ 0,28
			SRB : steel + glycerol – flat		0,18	≥ 0,18
	SRB : steel + glycerol – heel (contact angle 7°)		0,13	≥ 0,13		

