



by Honeywell

Technical Specifications

COMPLETE BOX 20 M / 30 M

Description:

Complete Box is composed of 1 Tree Pruning Harness, 1 chainsaw Karabiner, 1 Arborist Lanyard, 1 spike 1 Pic, 1 Reglex machoire 3 M.

References:

1003278 : 20 M

1003279 : 30 M

Features:

- **FEATURES FOR THE ARBORIST LANYARD**



Reference :

1003080 for 20 M

1003081 for 30 M

White rope:

Raw material: polyester

CS 20 karabiner :

Raw Material : aluminium

Weight: 0.1 kg

Breaking strength: > 2200 daN

Standard: EN 362

Snap hook karabiner :

Raw material: zinc steel

Opening: 18 mm

Weight: 0.302 kg

Breaking strength: > 2200 daN

Reglex 3000:

Raw material: stainless steel

Weight: 0.302 kg

Breaking strength: > 1500 daN

EN 358 : Work Positioning System



HONEYWELL FALL PROTECTION FRANCE SAS

35-37 rue de la Bidauderie

F - 18100 Vierzon - France

Tel : +33 2 48 52 40 40

Fax : +33 2 48 71 04 97

Web site : www.honeywellsafety.com



by Honeywell

Features for the Tree Pruning Harness

Reference :
1002927

3 - points Tree Pruning Harness with a large positioning belt and comfortable seat strap. : rear anchorage for fall arrest , sternal anchorage for climbing line and Side D-Rings for positioning lanyard.

Orange Webbing of the belt and harness

Width : 44 mm
Raw material: 100 % Polyamide
Breaking strength: > 2200 daN

Rear buckle and Side D-Rings buckles

Raw Material : Ø 7 mm galvanized steel
Belt and Seat Strap : in green cordura
Belt Buckles : in galvanized steel
Automatic buckle : in aluminium and Stainless Steel
Adjustment buckles : in aluminium

TEST :

Breaking strength: > 1500 daN
Weight: 1,780 kg

Temperature of use: -30°C to +50°C

EN 358 and EN 361



HONEYWELL FALL PROTECTION FRANCE SAS

35-37 rue de la Bidauderie
F - 18100 Vierzon - France
Tel : +33 2 48 52 40 40
Fax : +33 2 48 71 04 97

Web site : www.honeywellsafety.com



by Honeywell

- **FEATURES FOR THE REGLAX MACHOIRE 3 M**

Reference :
1003099

Positioning lanyard in Polypropylene Ø 14 mm galvanized steel core .Equipped with an adjuster with SS jaws and a double safety connector.

TEST:

Breaking strength : > 15 KN
Temperature : de -30°C à + 50°C
Weight : 1,620 kg

EN 358



- **FEATURES FOR THE SPIKE 1 PICS (REF 1002986): BY PAIR**

Galvanized steel adjustable gaff equipped with 1 short spike.
Comfortable leather pad with webbing fixing strap (can be replaced).

Weight : 2,4 kg



LAW of 19 MARCH 93

PPE are products classified in category III, mortal risks, and as such they have to be the object of a periodic inspection for less than twelve months at the time of its use by the qualified person.

For more information, please contact our technical team at 02 48 52 40 42 or by e-mail techniserv.hsp@honeywell.com

HONEYWELL FALL PROTECTION FRANCE SAS

35-37 rue de la Bidauderie

F - 18100 Vierzon - France

Tel : +33 2 48 52 40 40

Fax : +33 2 48 71 04 97

Web site : www.honeywellsafety.com